


SD-32 Series:



Specification

Type	SD - 32R		SD - 32N		SD - 32P
Characteristics	SD - 32R		SD - 32N		SD - 32P
Wiring	2Wire		3 Wire		
Connect Diagram					
Switching logic	Normally open		Solid state output, Normally open		
Output	Reed switch		NPN Sinking		PNP Sourcing
Lead wire type	Horizontal				
Load voltage	5 ~ 240V DC/AC		5~28V DC		
Load current	100mA Max.		200mA Max.		
Switching rating	10W Max.		6W Max.		
Current consumption	---		20mA Max.@ 24V		18mA Max.@ 24V
Voltage drop	2.5V Max.@ 40mA DC		0.5V Max.@ 200mA (Resistive load)		
Leakage current	---		0.01mA Max.		
Frequency	200Hz		1000Hz		
Shock	30G		50G		
Vibration	90 m/s ² (9G), Double amplitude 1.5 mm				
Insulation resistant	DC 500V 100MΩ (Lead wire to case)				
Withstand voltage	AC 1000V (50/60Hz) 1 minute (Lead wire to case)				
CE & Protection IP	EN60947-5-2 IEC529 IP67(NEMA 6)				
Indicator	Red LED				Green LED
Cable	2.8φ,2C, Gray PVC		2.8φ,3C, Black PVC		
Temperature range	-10 ~ 70				
Protection circuit	---		Reverse polarity; Surge suppression		
Dimensions	SD-32R SD-32R-M8QD SD-32R-M12QD		SD-32N SD-32N-M8QD SD-32N-M12QD		SD-32P SD-32P-M8QD SD-32P-M12QD
			M8 (2-Wire QD Link)		M8 (2-Wire E-QD Link)
			M8 (3-Wire QD Link)		M12 (3-Wire QD Link)
M8&M12-Connector					